



QUALITÄT IN DER  
BEFESTIGUNGSTECHNIK

BEVER GmbH · Auf dem niedern Bruch 12 · D-57399 Kirchhundem-Würdinghausen

## DECLARATION OF PERFORMANCE

DoP No. 201305-002-E

1. Unique identification code of the product-type: **Universal Threaded Cavity wall tie, plug cavity wall tie with nail top**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4): **Universal Threaded Cavity wall tie and plug cavity wall tie with nail top in the sizes of 4 x 160 to 4 x 300 mm, designation see packaging of the product**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**asymmetrically wall ties for horizontal installation for connection of two leaves in a cavity wall, it is used to fix brickwork or blockwork to timber framed structures**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5)  
**BEVER GmbH, Auf dem niederm Bruch 12, 57399 Kirchhundem**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2): -----
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3 according DIN EN 845-1-2012-10**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**The initial type testing in accordance with System 3 was performed by the notified body MPA Bau Hannover, Nienburger Str. 3, 30167 Hannover - identification number 0764**
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: -----
9. Declared performance:  
**tensile load capacity in timber VH C 24 and mortar class M2.5 : 1700 N**  
**compression load capacity for cavity width up to 200 mm: 1350 N**  
**minimum embedment depth in the mortar joint of the brick façade: 50 mm**  
**assurance against punching: 35 mm**  
**Water shedding capacity: resistant**  
**durability: 1**  
**dangerous substance: NPD**

../2



../2

10.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Klemens Grawe, BEVER GmbH**

Kirchhundem, 31.07.2013

A handwritten signature in blue ink, consisting of a stylized 'K' followed by a series of loops and a horizontal line at the bottom. To the left of the signature, the letters 'Mo.' are written in a similar blue ink.